



## Ordering Information

# Reduced Wall Aluminum Flexible Metal Conduit


### Description

- Lightweight Reduced Wall Aluminum Flexible Conduit
- Premium aluminum alloy
- Interlocking design

### Applications

- Flexible metal raceway for electrical power, control and communication cables
- Motor leads
- Listed assemblies
- Listed wire fixtures
- Manufactured wiring systems

Interlocking Aluminum Armor



### References & Ratings

- UL 1, UL 1479, File Reference E11831, CSA File Number 15035, CSA C22.2 No. 56 (trade size 3/8 only)
- Federal Specification WW-C-566C, (now superseded by UL 1)
- NEC® 250.118(6), 300.22(C), 348, 430.123, 501.4(B)(2), 645.5
- Cable Tray installations per NEC®
- Environmental Air-Handling space installation NEC® 300.22(C)
- UL Classified 1, 2 and 3-hour Through-Penetration Fire Systems UL File R14141

## Ordering Information

## Product Dimensions/ Bend Radius

Product Code	Trade Size (inches)	Trade Size (mm)	Coil Length (feet)	Reel Length (feet)	Approx. Weight/ 100 feet (pounds)	Internal Diameter (min/max) inches	External Diameter (min/max) inches	Bend Radius (inches)
5601-22-00+	3/8	12	25'	—	6	0.375/0.393	0.560/0.610	2
5601-24-00+	3/8	12	50'	—	6	0.375/0.393	0.560/0.610	2
5601-30-00+	3/8	12	100'	—	6	0.375/0.393	0.560/0.610	2
5601-42-00+	3/8	12	250'	—	6	0.375/0.393	0.560/0.610	2
5601-45-00+	3/8	12	—	500'	6	0.375/0.393	0.560/0.610	2
5601-60-00+	3/8	12	—	1000'	6	0.375/0.393	0.560/0.610	2
5602-22-00	1/2	16	25'	—	10	0.625/0.645	0.860/0.920	3
5602-24-00	1/2	16	50'	—	10	0.625/0.645	0.860/0.920	3
5602-30-00	1/2	16	100'	—	10	0.625/0.645	0.860/0.920	3
5602-45-00	1/2	16	—	500'	10	0.625/0.645	0.860/0.920	3
5602-60-00	1/2	16	—	1000'	10	0.625/0.645	0.860/0.920	3
5603-22-00	3/4	21	25'	—	12	0.812/0.835	1.045/1.105	4
5603-24-00	3/4	21	50'	—	12	0.812/0.835	1.045/1.105	4
5603-30-00	3/4	21	100'	—	12	0.812/0.835	1.045/1.105	4
5603-45-00	3/4	21	—	500'	12	0.812/0.835	1.045/1.105	4
5603-60-00	3/4	21	—	1000'	12	0.812/0.835	1.045/1.105	4
5604-24-00	1	27	50'	—	18	1.000/1.040	1.300/1.380	5
5604-80-00	1	27	—	300'	18	1.000/1.040	1.300/1.380	5
5605-24-00	1¼	35	50'	—	22	1.250/1.300	1.550/1.630	6.25
5605-40-00	1¼	35	—	200'	22	1.250/1.300	1.550/1.630	6.25
5606-22-00	1½	41	25'	—	26	1.500/1.575	1.850/1.950	7.50
5607-22-00	2	53	25'	—	35	2.000/2.080	2.350/2.450	10
5608-22-00	2½	63	25'	—	57	2.500/—	2.860/3.060	12.50
5609-22-00	3	78	25'	—	68	3.000/—	3.360/3.560	15
5610-22-00	3½	91	25'	—	80	3.500/—	3.860/4.060	17.50
5611-22-00	4	103	25'	—	91	4.000/—	4.360/4.560	20

NOTE: All dimensions and weights are subject to normal manufacturing tolerances.

+CSA certified

Review NEC® 250.118(6) for grounding requirements.